BEST AVAILABLE COPY

Fax: 23698454

May 4 '05 16:22

P. 03/10

Customer No.: 31561 Application No.: 10/711,514 Docket No.: 13621-US-PA

AMENDMENTS

In the Claims:

1. (currently amended) A method for programming a non-volatile memory, comprising:

giving a level distribution of a plurality of memory cells in a storage state in the non
volatile memory:

selecting a reference level according to-a the given level distribution-of-a plurality of memory cells in a storage state in the non velatile memory; and

programming making a plurality of predetermined memory cells to have a cell level distribution of a next storage state according to the reference level, wherein

the reference level falls between the cell level distribution of the memory cells in the current storage state and the cell level distribution of the memory cells in the next storage state.

- 2. (original) The method of claim 1, wherein the levels of the memory cells in the next storage state are higher than the levels of the memory cells in the current storage state, and the reference level falls between a highest level of the memory cells in the current storage state and a lowest level of the memory cells in the next storage state.
 - 3. (original) The method of claim 2, wherein selecting the reference level comprises: predetermining a plurality of candidate reference levels; and

selecting one candidate reference level from the candidate reference levels whose levels are higher than the highest level of the memory cells in the storage state as the reference level.

Customer No.: 31561 Application No.: 10/711,514 Docket No.: 13621-US-PA

- 4. (original) The method of claim 1, wherein the non-volatile memory is a one-time programmable (OTP) memory, a multi-time programmable (MTP) memory, a multi-level cell (MLC) memory, or a programmable resistor with erase-less memory (PREM).
- 5. (original) The method of claim 1, wherein the storage state of a memory cell depends on its cell current, and the reference level is a current reference level.
- 6. (original) The method of claim 1, wherein the storage state of a memory cell depends on its threshold voltage, and the reference level is a threshold voltage reference level.
- 7. (currently amended) A method for programming a multi-level ceil (MLC) non-volatile memory whose memory cells having a first storage state up to an Nth storage state in an ascending order of level, the method comprising:
 - (a) giving a level distribution of the memory cells in an ith storage state;
- (a) (b) selecting an ith reference level according to—a the given level distribution of the memory cells in—an the ith storage state;
- (b) (c) programming making a plurality of memory cells to have a cell level distribution of a (i+1)th storage state according to the ith reference level; and

repeating steps (a)-and (b) to (c) until programming of the Nth storage state is completed, wherein an initial value of i is 1, the value of i is incremented by 1 before each repetition, and the ith reference level falls between a highest level of the memory cells in the ith storage state and a lowest level of the memory cells in the (i+1)th storage state.

8. (original) The method of claim 7, further comprising:

Fax:23698454 May 4 '05 16:23

Customer No.: 31561 Application No.: 10/711,514 Docket No.: 13621-US-PA

predetermining a plurality of candidate reference levels before steps (a) and (b); and step (a) comprising:

selecting one candidate reference level from the candidate reference levels whose levels are higher than a highest level of the memory cells in the ith storage state as an ith reference level.

- 9. (original) The method of claim 7, wherein the storage state of a memory cell depends on its threshold voltage, and the reference level is a threshold voltage reference level.
- 10. (original) The method of claim 7, wherein the storage state of a memory cell depends on its cell current, and the reference level is a current reference level.
- 11. (original) The method of claim 10, wherein the MLC non-volatile memory comprises a programmable resistor with erase-less memory (PREM).
- 12. (currently amended) A method for programming a multi-time programmable (MTP) non-volatile memory, comprising:

giving a level distribution of memory cells of the MTP non-volatile memory;

selecting a reference level according to a the given level distribution of the memory cells of the MTP non-volatile memory;

resetting a storage state of each of the memory cells to a first storage state; and

programming making a plurality of predetermined memory cells—to have a cell level

distribution of a second storage state according to the reference level,

wherein the reference level falls between a highest level of the memory cells in the first storage state and a lowest level of the memory cells in the second storage state.

May 4 '05 16:23 P.06/10

Customer No.: 31561 Application No.: 10/711,514 Docket No.: 13621-US-PA

13. (original) The method of claim 12, wherein selecting the reference level comprises: predetermining a plurality of candidate reference levels; and

Fax:23698454

selecting one candidate reference level from the candidate reference levels whose level are higher than the highest level of the memory cells as the reference level.

- 14. (original) The method of claim 12, wherein the storage state of a memory cell depends on its threshold voltage, and the reference level is a threshold voltage reference level.
- 15. (original) The method of claim 12, wherein the storage state of a memory cell depends on its cell current, and the reference level is a current reference level.
- 16. (original) The method of claim 15, wherein the MTP non-volatile memory comprises a programmable resistor with erase-less memory (PREM).

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.